



Version with Markings to  
Show Changes Made

~~TITLE OF THE INVENTION~~

DATA PROCESSOR

BACKGROUND OF THE INVENTION

5 | 1. Field of the Invention

[0001] The present invention relates to data processors and, more specifically, to data processors for processing data with a digital signature coming from a server connected over a network.

10 | 2. Description of the Background Art

[0002] In recent years, the number of computers that are connected over the Internet has been rapidly increasing, and WWW (World Wide Web; simply "Web" ~~in the below~~ hereinbelow) browsing has become very popular through mobile phones, for example. As  
15 | to data processors for Web browsing, various technologies have been known.

[0003] A first technique ~~is relating~~ relates to a JAVA applet. The JAVA applet is a program written in JAVA, and ~~operating~~ operates on various devices connected over the network. The user uses  
20 | browser software to download such a JAVA applet for execution. The issue here ~~is,~~ is that it is considered inappropriate in view of system safety that the JAVA applet which is freely downloadable, accesses ~~device~~ peripheral device equipment or reads/writes from/to I/O (input/output) ports of the device. Thus, the JAVA  
25 | applet is allowed to limitedly access predetermined data in the

Version with Markings to  
Show Changes Made

device, and this means that the JAVA applet is generally not allowed to access peripheral device ~~peripheral~~-equipment or read/write from/to I/O ports. As a technique to enable the JAVA applet to access peripheral equipment, Japanese Patent Laid-Open Publication No. 2000-112864 discloses ~~as~~ incorporating in advance a driver of the peripheral equipment into a library which is used by the JAVA applet.

[0004] A second technique ~~is relating~~ relates to digital signature. Web browsing has conventionally been ~~conventionally~~ for content download and display, and recently for online shopping and online trading, and the like. To exchange data for such commercial purpose, data transmission/reception requires much higher reliability. Thus, at data reception, the identity of the sender of the data and any possibility of data tampering due to hacking done by outsiders have to be checked, and if the data is found to be erroneous, the data should not be processed. As a method of insuring the high reliability for data transmission/reception, the following digital signature system using a public key cryptosystem has been known.

[0005] In such a digital signature system, a device on the transmission end hashes transmitting data (hereinafter, refers to as "text") by using a one-way function. The resultant hash value is encrypted by using a private key, and the thus encrypted result is referred to as a "signature". The device on the transmission end then attaches this signature and a public key

which is paired off with the private key to the text for transmission.

On the reception end, the received text is hashed by using a one-way function, and the signature attached to the text is decrypted by using the public key which is also attached to the text. Through comparison between the result derived by decrypting the signature and the result derived by hashing the text, if those are the same, the text is transmitted from the transmission end having the private key, and the text is also proved that no data tampering has occurred thereto during communications.

10 [0006] In this system, the text is hashed in its entirety by using a one-way function at the time of signature generation and authentication. Thus, if the text is large in data amount, the processing load is increased, and ~~resultantly~~ the processing time resultantly takes longer. This causes a problem for mobile units  
15 which are relatively low in processing capacity. For ~~betterment,~~ improvement, instead of hashing the text in its entirety, there is a method which is conventionally known to hash only any significant part which should not be tampered. In this method, data is first arranged separately in a part that is to be hashed  
20 for signature generation (hereinafter, refers to as "protected data region" in view of protecting it from tampering), and a part that is not to be hashed (hereinafter, refers to as "unprotected data region"). ~~And only~~ Only the data included in the protected data region is used for signature generation and authentication.  
25 That is, the data included in the protected data region is checked

for any possibility of tampering by using a digital signature, and the data in the unprotected data region is not checked for a digital signature. In this manner, as compared with the case where the text is checked in its entirety for a digital signature, the processing load and the processing time can be suppressed.

**[0007]** A third technique ~~is relating~~ relates to signature authorization control for digital signature. This signature authorization control is done to control which data can be signed by which signer, and is considered quite important in terms of system design. However, there is no method so far of controlling signature authorization based on the data type. Therefore, most of the time, information about which signer is authorized to sign what data type has been implicitly and proprietarily determined on a system basis. Also, certificates are roughly classified under classes and usage provided by certificate authorities, and their interpretations are appropriately defined on an application basis.

**[0008]** However, those conventional technologies do not solve the following problems which are associated with data processors for Web browsing. As to the technology relating to the JAVA applet, the method disclosed in the ~~above-mentioned~~ above-mentioned publication is not applicable to devices such as mobile phones and portable information terminals. This is ~~because,~~ because such devices cannot be newly provided with a JAVA library once they are shipped, and the JAVA library for accessing peripheral equipment has to be previously incorporated before the devices

are shipped. By doing so, however, every user is allowed to use such a JAVA library for accessing other users' peripheral equipment. For example, the mobile phones store ~~user~~users' personal information such as telephone numbers and addresses. No ~~authorized~~unauthorized user should ~~not~~ be allowed to access such personal information. In this viewpoint, the method in the above publication is not applicable to devices such as mobile phones to which no JAVA library can be newly provided once the devices are shipped.

10 **[0009]** As to the technique relating to digital signature, by separately arranging the text into the protected data region and the unprotected data region, the load of applications on the reception end is resultantly increased. This is ~~because~~, because the reception end has to always make it clear for the received ~~data,~~ data whether ~~it~~ the received data has been included in the protected data region or the unprotected data region for processing. For example, on the reception end, in the case where the data which is supposed to be in the protected data region is found in the unprotected data region, the data should not be processed in the same manner as to the case where the data is in the protected data region. On the reception end, application programs are used to clarify from which data region the data has come. Accordingly, in this method of segmenting the data region, the load of the applications on the reception end is increased when the data is large in data amount.

8                    4

[0010]      To solve this problem, there is a possibility of determining in advance, with mutual understanding between the transmission and reception ends, what data should go to which data region, i.e., the protected data region, and the unprotected data region. In such a manner as fixedly determining the protected and unprotected data regions, however, if the data is changed in its significance, that is, if the data so far included in the unprotected data region needs to be included in the protected data region not to be tampered, applications on the reception end have to be changed. Therefore, data cannot be freely added or changed in state, protected or unprotected.

[0011]      As to the technique relating to signature authorization control, data requiring high reliability has been recently increasing in type, as exemplified by data for e-commerce. Accordingly, no matter what type and how many, there ~~requires~~ is a requirement to determine the signer's authorization in the same manner. Most of the time, the data types are corresponding to data usage and processing that is to be executed on the reception end at the time of data reception. Regardless of such a correspondence, however, there has been no common rule for defining the signer's signature authorization. As a result, for every new data type, a logic for defining which signer has an authorization for signing the new data type has to be implemented in every data processor.

25

## SUMMARY OF THE INVENTION

[0012] Therefore, a first object of the present invention is to provide data processors ~~accessible to~~ that can safely access peripheral equipment ~~safely by~~ allowing only privileged programs to access the peripheral equipment.

[0013] A second object of the present invention is to provide data processors which are capable of reducing the load of applications even if a data region is segmented into protected and unprotected data regions, and detecting whether data included in the unprotected data region has been tampered with.

[0014] A third object of the present invention is to provide data processors which are capable of determining whether a signer is authorized for signing the received data in the same manner regardless of data type.

[0015] The present invention has the following features to attain the objects above.

[0016] A first aspect of the present invention is directed to a data processor which is supplied with command data specifying a data component to be used for controlling ~~itself, the data~~ processor, and operates based on the command ~~data, the~~ data. The data processor ~~comprising:~~ of the first aspect comprises: a ~~transmission/reception section for transmitting/receiving~~ transmitter/receiver operable to transmit/receive data to/from a server connected over a network; a validity determination ~~section~~ for determining unit operable to determine whether the command

data is valid; a command data processing ~~section for retrieving,~~  
unit operable to retrieve, when the validity determination unit  
determines that the command data is determined as valid, by the  
~~validity determination section,~~ the data component specified by  
5 the command data from the server by using the  
~~transmission/reception section; transmitter/receiver;~~ and a data  
component processing ~~section for controlling~~ unit operable to  
control the data processor based on the data component retrieved  
by the command data processing ~~section~~ unit. As such, according  
10 to the first aspect, data for controlling the data processor is  
retrieved based on the command data which is determined as valid.  
Therefore, the device control can be securely done.

[0017] In this case, the data component processing ~~section~~ unit  
may perform a screen display based on the data component retrieved  
15 by the command data processing ~~section~~ unit, or may output the  
data component retrieved by the command data processing ~~section~~  
unit to the outside of the data processor. In this manner, screen  
display and data output can be securely done. Further, the data  
component used for controlling the data processor by the data  
20 component processing ~~section~~ unit may be limited to be the data  
component that is retrieved by the command data processing section.  
As such, by allowing the data which is used for controlling the  
data processor to be updated only in a fixed procedure, the data  
processor can be controlled in a safe manner.

25 [0018] Also, the command data may be encrypted, and the validity



determination ~~section-unit~~ may determine whether the command data is valid after decrypting ~~it~~ the command data. ~~Or, Alternatively,~~ the command data processing ~~section-unit~~ may determine whether the data component retrieved from the server is valid, and when the data component is determined to be valid, supply data component to the data component processing ~~section-unit~~. In such a manner, the data processor can be controlled in a safer manner.

[0019] Preferably, the command data processing ~~section-unit~~ may include a language processing ~~section for interpreting-unit~~ operable to interpret a JAVA language, and a JAVA applet to be processed by the language processing ~~section-unit~~. More preferably, the ~~transmission/reception-section~~ transmitter/receiver may receive, in accordance with a user's instruction, the JAVA applet included in the command data processing ~~section-unit~~. In such a structure, by processing the command data following the JAVA applet (especially the one retrieved through communications), the contents of the command data can be changed flexibly. Further, the ~~transmission/reception-transmitter/receiver~~ may receive, in accordance with a user's instruction, the command data ~~for supply to be supplied~~ to the validity determination ~~section-unit~~. If so, the data processor has no more need to store ~~therein~~ the command data therein, and may retrieve ~~it~~ the command data through communications for processing.

[0020] A second aspect of the present invention is directed

to a data processor which is supplied with command data including  
a data component used for controlling ~~itself~~ that data processor,  
and operates based on the command data, ~~the~~ data. The data  
processor ~~comprising:~~ of the second aspect comprises: a  
5 ~~transmission/reception section for transmitting/receiving~~  
transmitter/receiver operable to transmit/receive data to/from  
a server connected over a network; a validity determination ~~section~~  
~~for determining~~ unit operable to determine whether the command  
data is valid; a command data processing ~~section for retrieving,~~  
10 unit operable to retrieve, when the validity determination unit  
determines that the command data is ~~determined as valid,~~ by the  
~~validity determination section,~~ the data component included in  
the command data; and a data component processing ~~section for~~  
~~controlling~~ unit operable to control the data processor based on  
15 the data component retrieved by the command data processing ~~section~~  
unit. As such, according to the second aspect, the data for  
controlling the data processor is retrieved based on the command  
data which is determined as valid. Therefore, the device control  
can be securely done.

20 **[0021]** In such a case, the data component processing ~~section~~  
unit may perform a screen display based on the data component  
retrieved by the command data processing ~~section~~ unit, or may output  
the data component retrieved by the command data processing ~~section~~  
unit to the outside of the data processor. Thereby, screen display  
25 and data output can be securely done. Moreover, the data component

used for controlling the data processor by the data component processing ~~section-unit~~ may be limited to be the data component retrieved by the command data processing ~~section-unit~~. As such, by allowing the data which is used for controlling the data processor to be updated only in a fixed procedure, the data processor can be controlled in a safe manner.

[0022] Also, the command data may be encrypted, and the validity determination ~~section-unit~~ may determine whether the command data is valid after decrypting ~~it~~ the command data. If so, the data processor can be controlled in a safer manner.

[0023] Preferably, the command data processing ~~section-unit~~ may include a language processing ~~section-for interpreting-unit~~ operable to interpret a JAVA language, and a JAVA applet to be processed by the language processing ~~section-unit~~. More

preferably, the transmission/reception section may receive, in accordance with a user's instruction, the JAVA applet included in the command data processing section. In such a structure, by processing the command data following the JAVA applet (especially the one that is retrieved through communications), the contents

of the command data can be changed flexibly. Alternatively, the ~~transmission/reception section~~ transmitter/receiver may receive, in accordance with a user's instruction, the command data for ~~supply~~ to be supplied to the validity determination ~~section-unit~~. If so, the data processor has no more need to store ~~therein~~ the command data therein, and may retrieve ~~it~~ the command data through

communications for processing.

[0024] A third aspect of the present invention is directed to a data processing method in which command data specifying a data component to be used for controlling a data processor is supplied, and the command data is used as a basis for an operation, the operation. The method comprising: of the third aspect comprises: a transmission/reception step of transmitting/receiving data to/from a server connected over a network; a validity determination step of determining whether the command data is valid; a command data processing step of retrieving, when the command data is determined as valid in the validity determination step, the data component specified by the command data from the server by calling for the transmission/reception step; and a data component processing step of controlling the data processor based on the data component retrieved in the command data processing step. As such, according to the third aspect, data for controlling the data processor is retrieved based on the command data which is determined as valid. Therefore, the device control can be securely done.

[0025] A fourth aspect of the present invention is directed to a data processing method in which command data including a data component used for controlling a data processor is supplied, and the command data is used as a basis for an operation, the operation. The method comprising: of the fourth aspect comprise: a transmission/reception step of transmitting/receiving data to/from a server connected over a network; a validity determination

step of determining whether the command data is valid; a command data processing step of retrieving, when the command data is determined as valid in the validity determination step, the data component included in the command data; and a data component processing step of controlling the data processor based on the data component retrieved in the command data processing step. As such, according to the fourth aspect, data for controlling the data processor is retrieved from the command data which is determined as valid. Therefore, the device control can be securely done.

**[0026]** A fifth aspect of the present invention is directed to a data processor for receiving and processing data to which information for tampering detection is added, ~~the added.~~ The data processor comprising: a reception section for receiving of the  
15 fifth aspect comprises: a receiver operable to receive data which includes an authentication information region for including the tampering detection information, a protected data region for including data to be subjected to tampering detection, and an unprotected data region for including data that is not to be  
20 subjected to tampering detection, wherein the protected data region includes an unprotection list which lists, by type, the data included in the unprotected data region; a protected data authentication ~~section for detecting,~~ unit operable to detect,  
for the data received by the ~~reception section,~~ receiver, whether  
25 the data included in the protected data region has been tampered

with by using the tampering detection information included in the authentication information region; and an unprotected data authentication section ~~for authenticating, unit operable to authenticate~~ for the data received by the ~~reception section receiver~~, whether the data included in the unprotected data region is valid based on the unprotection list which has been confirmed as not having been tampered with by the protected data authentication-section ~~unit~~. In this case, the data received by the ~~reception section receiver~~ may be hypertext data, and the unprotection list may list, by type, a tag included in the unprotected data region.

**[0027]** As described above, in the fifth aspect, as compared with the case where the data is subjected to data signature in its entirety, the data amount to be used for signature authentication can be reduced, successfully improving the efficiency for signature authentication. Moreover, the data (or tag) included in the unprotected data region can be increased in reliability. Further, the application has no need to know whether the data (or tag) has been included in which of the protected data region or the unprotected data region for processing the received data. As a result, the application can be reduced in processing amount, thereby ~~rendering~~ increasing the processing speed ~~increased~~.

**[0028]** A sixth aspect of the present invention is directed to a data processor which is structured by a transmitting data

processor and a receiving data processor, wherein the processor.  
The transmitting data processor transfers is operable to transfer,  
to the receiving data processor, data to which information for  
tampering detection is added, wherein the added. The transmitting  
5 data processor comprises: an unprotection list generation section  
~~for generating unit operable to generate~~ an unprotection list which  
lists, by type, data that is not to be subjected to tampering  
detection; a data generation section ~~for generating unit operable~~  
to generate data to be transmitted by arranging data to be subjected  
10 to tampering detection in a protected data region together with  
the unprotection list, the data not to be subjected to tampering  
detection in an unprotected data region, and the tampering  
detection information derived based on the data in the protected  
data region in an authentication information region; and a  
15 transmission section ~~for transmitting unit operable to transmit~~  
the data generated by the data generation section, and the section.  
The receiving data processor comprises: a reception section ~~for~~  
~~receiving receiver operable to receive~~ the data transmitted from  
the transmitting data processor; a protected data authentication  
20 section ~~for detecting unit operable to detect~~, for the data received  
by the ~~reception section receiver~~, whether the data in the protected  
data region has been tampered with by using the tampering detection  
information in the authentication information region; and an  
unprotected data authentication section ~~for authenticating unit~~  
25 operable to authenticate, for the data received by the ~~reception~~

section receiver, whether the data included in the unprotected data region is valid based on the unprotection list which has been confirmed as not having been tampered with by the protected data authentication ~~section~~ unit. If this is the case, the data generated by the data generation ~~section~~ unit may be hypertext data, and the unprotection list may list, by type, a tag which is included in the unprotected data region.

[0029] As such, in the sixth aspect, in addition to the effects of the fifth aspect, data (or tag) can be appropriately changed in state, protected or unprotected, without changing applications in data processors on the reception end. Thus, data handling can be freely changed.

[0030] A seventh aspect of the present invention is directed to a data processing method for receiving and processing data to which information for tampering detection is ~~added, the~~ added.

~~The method comprising:~~ of the seventh aspect comprises: a reception step of receiving data which includes an authentication information region for including the tampering detection information, a protected data region for including data to be subjected to tampering detection, and an unprotected data region for including data that is not to be subjected to tampering detection, wherein the protected data region includes an unprotection list which lists, by type, the data included in the unprotected data region; a protected data authentication step of detecting, for the data received in the reception step, whether the data included in the



protected data region has been tampered with by using the tampering detection information included in the authentication information region; and an unprotected data authentication step of authenticating, for the data received in the reception step, whether the data included in the unprotected data region is valid based on the unprotection list which has been confirmed as not having been tampered with in the protected data authentication step.

**[0031]** As described above, in the seventh aspect, as compared with the case where the data is subjected to data signature in its entirety, the data amount to be used for signature authentication can be reduced, thereby successfully improving the efficiency for signature authentication. Moreover, the data included in the unprotected data region can be increased in reliability. Further, the application has no need to know whether the data has been included in which of the protected data region or the unprotected data region for processing the received data. As a result, the application can be reduced in processing amount, thereby ~~rendering~~ increasing the processing speed ~~increased~~.

**[0032]** An eighth aspect of the present invention is directed to a data processing method for transferring data to which information for tampering detection is added from a transmitting data processor to a receiving data processor, ~~wherein~~ processor. In the method of the eighth aspect, the transmitting data processor performs: an unprotection list generation step of generating an

unprotection list which lists, by type, data that is not to be subjected to tampering detection; a data generation step of generating data to be transmitted by arranging data to be subjected to tampering detection in a protected data region together with  
5 | the generated unprotection list, the data that is not to be subjected to tampering detection in an unprotected data region, and the tampering detection information derived based on the data in the protected data region in an authentication information region; and a transmission step of transmitting the data generated in the  
10 | ~~data generation step, and~~ step. In the method of the eighth aspect, the receiving data processor performs: a reception step of receiving the data transmitted from the transmitting data processor; a protected data authentication step of detecting, for the data received in the reception step, whether the data in the  
15 | protected data region has been tampered with by using the tampering detection information in the authentication information region; and an unprotected data authentication step of authenticating, for the data received in the reception step, whether the data included in the unprotected data region is valid based on the  
20 | unprotection list which has been confirmed as not having been tampered with in the protected data authentication step.

**[0033]** As such, in the eighth aspect, in addition to the effects of the seventh aspect, data (or tag) can be appropriately changed in state, protected or unprotected, without changing applications  
25 | in data processors on the reception end. Thus, data handling can

be freely changed.

[0034] A ninth aspect of the present invention is directed to a data processor for receiving and processing data with a digital signature, ~~comprising: a reception section for receiving signature.~~

5    The data processor of the ninth aspect comprises: a receiver  
operable to receive the data with the digital signature from a  
server connected over a network; a signer certificate acquiring  
section for acquiring unit operable to acquire a signer certificate  
10    indicating, by type, what data is signable by a signer of the data  
received by the reception section receiver; and a signature  
authentication section for determining unit operable to determine,  
when the signer certificate acquired by the signer certificate  
acquiring section unit indicates, by type, the data received by  
the reception section receiver, that a signature applied to the  
15    data as valid. As such, according to the ninth aspect, it can  
be determined whether the signer has an authorization for signing  
the received data by using the same algorithm for any arbitrary  
data type.

[0035] In such a case, the signer certificate may include, in  
20    a list, by type, a plurality of the signable data. With such a  
structure, only a single signer certificate can be used to represent  
that the signer has an authorization for signing the data varying  
in type. Further, the signer certificate can include a wildcard  
as a type of the signable data, and when the signer certificate  
25    acquired by the signer certificate acquiring section includes the

wildcard as the type of the signable data, the signature authentication ~~section determines unit~~ is operable to determine that the signature applied to any data received in the ~~reception section as receiver~~ is valid. In this manner, the signer certificate has no need to list every data type to indicate that the signer has the authorization for signing all of the data types.

[0036] Moreover, the signature authentication ~~section unit~~ may acquire a type of the data based on a characteristic part of a URI (Uniform Resource Identifier) of the data received by the ~~reception section receiver~~, or may acquire the type of the data based on a header part of the data received by the ~~reception section receiver~~. In this manner, by comparing, as character strings, the characteristic part of the URI of the data (or data type identification information included in the header part at the time of data reception) with the signable data type included in the signer certificate, it will be determined whether or not the signer has an authorization for signing the received data.

[0037] Moreover, the signer certificate acquiring ~~section unit~~ may receive the signer certificate by using the ~~reception section receiver~~. If so, there is no need to possess the signer certificate beforehand, and by receiving the signer certificate, a determination can be made as to whether the signer has an authorization for the received data.

[0038] A tenth aspect of the present invention is directed to a data processing method for receiving and processing data with

a digital signature, comprising: signature. The method of the tenth aspect comprises a reception step of receiving the data with the digital signature from a server connected over a network; a signer certificate acquiring step of acquiring a signer certificate indicating, by type, what data is signable by a signer of the data received in the reception step; and a signature authentication step of determining, when the signer certificate acquired in the signer certificate acquiring step indicates, by type, the data received in the reception step, that a signature applied to the data as valid. As such, according to the tenth aspect, by applying the same algorithm to any arbitrary data type, it can be determined whether the signer has an authorization for signing the received data.

[0039] These and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0040] FIG. 1 is a diagram showing the structure of a communications system including a data processor according to any one of the first to fifth embodiments of the present invention;

FIG. 2 is a block diagram showing the hardware structure shared among the data processors of the first to third, and fifth embodiments;

FIG. 3 is a block diagram showing the structure of the data processor of the first embodiment;

FIG. 4 is a flowchart showing the operation of the data processor of the first embodiment;

5           FIG. 5 shows exemplary command data in the data processor of the first embodiment;

FIG. 6 shows exemplary terminal data in the data processor of the first embodiment;

10           FIG. 7 is a flowchart showing a command data analyzing process in the data processor of the first embodiment;

FIG. 8 shows an exemplary result of analyzing the command data in the data processor of the first embodiment;

FIG. 9 is a flowchart showing a command data validity determining process in the data processor of the first embodiment;

15           FIG. 10 is a flowchart showing an operation controlling process in the data processor of the first embodiment;

FIG. 11 is an illustration showing how a display screen changes as a result of updating the terminal data in the data processor of the first embodiment;

20           FIG. 12 is a block diagram showing the structure of the data processor of the second embodiment of the present invention;

FIG. 13 is a flowchart showing the operation of the data processor of the second embodiment;

25           FIG. 14 shows exemplary command data in the data processor of the second embodiment;

FIG. 15 shows an exemplary result of analyzing the command data in the data processor of the second embodiment;

FIG. 16 is a flowchart showing an operation controlling process in the data processor of the second embodiment;

5        FIG. 17 is a block diagram showing the structure of the data processor of the third embodiment of the present invention;

FIG. 18 is a diagram showing the structure of data to be processed by the data processor of the third embodiment;

10       FIG. 19 is a diagram showing the structure of XML data to be processed by the data processor of the third embodiment;

FIG. 20 is a flowchart showing the operation of the data processor of the third embodiment;

FIG. 21 is a block diagram showing the structure of the data processor of the fourth embodiment of the present invention;

15       FIG. 22 is a diagram showing the structure of XML data to be processed by the data processor of the fourth embodiment;

FIG. 23 is a block diagram showing the structure of the data processor of the fifth embodiment of the present invention;

20       FIG. 24 shows an exemplary content to be processed by the data processor of the fifth embodiment; and

FIG. 25 shows an exemplary signer certificate to be referred to by the data processor of the fifth embodiment.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

25    **[0041]**    FIG. 1 is a diagram showing the structure of a

communications system including a data processor according to any one of the first to fifth embodiments of the present invention. In FIG. 1, a server 1 and a mobile unit 20 are both connected to a communications network 10, which includes the Internet 11, a gateway server 12, a mobile communications network 13, and a base station 14. The server 1 carries information written in languages for HyperText such as HTML (HyperText Markup Language) and XML (eXtended Markup Language) and image information, and is connected to the Internet 11. The mobile unit 20 performs digital wireless communications using CDMA (Code Division Multiple Access) between the base station 14 connected to the mobile communications network 13, for example. The gateway server 12 connects the Internet 11 and the mobile communications network 13 to each other. The mobile unit 20 makes an information request to the server 1 in response to the user's operation, and accordingly receives the requested information from the server 1. The mobile unit 20 supplies ~~thus~~ the received information to any predetermined application program, or displays the information on its screen. Here, ~~as is~~ although not shown in FIG. 1, in the typical communications system, the communications network 10 is connected with a plurality of servers 1 and a plurality of mobile units 20.

**[0042]** FIG. 2 is a block diagram showing the hardware structure of the mobile unit 20 of FIG. 1. As shown in FIG. 2, the mobile unit 20 includes an antenna 21, a wireless control section 22, a modulation section 23, a demodulation section 24, a channel codec



25, a sound input section 26, a sound output section 27, an input section 28, a display section 29, and an application execution section 30. The wireless control section 22 has two functions of: superimposing modulated data coming from the modulation section 23 onto a wireless carrier for transmission from the antenna 21; and receiving a signal in a predetermined frequency band from a high-frequency signal induced by the antenna 21. The modulation section 23 modulates data outputted from the channel codec 25 in a given manner for output to the wireless control section 22. The demodulation section 24 demodulates the signal received by the wireless control section 22 in a given manner, and outputs the resultant signal to the channel codec 25. In the channel codec 25, the signal outputted from the demodulation section 24, and signals coming from the sound input section 26 and the application execution section 30 are coded/decoded in a given manner. The data outputted from the demodulation section 24 is forwarded to either the sound output section 27 or the application execution section 30. The sound signal outputted from the sound input section 26 is forwarded to either the modulation section 23 or the application execution section 30. The data outputted from the application execution section 30 is forwarded to either the modulation section 23 or the sound output section 27.

**[0043]** The sound input section 26 is composed of a microphone, for example, and outputs an incoming sound signal to the channel codec 25. The sound output section 27 is composed of a speaker,

for example, and outputs data coming from the channel codec 25 by sound. The input section 28 is composed of a keyboard or buttons, for example, and outputs to the channel codec 25 operation data that is inputted through a display screen or dial numbers through push buttons. The display section 29 is composed of a display device, for example, and outputs data coming from the application execution section 30 for a screen display, or in a vibrating alert mode, for example.

**[0044]** The application execution section 30 includes a CPU 31, a RAM 32, and a ROM 33. The RAM 32 is a working memory for the CPU 31. The ROM 33 stores programs to be executed by the CPU 31, and data to be referred to by the CPU 31, or the like. The CPU 31 executes the programs stored in the RAM 32 or the ROM 33 while using the RAM 32 as a working memory. In this manner, the application execution section 30 performs various types of processes, e.g., connection control to the communications network 10, generation of transmitting data, display and storage of received data, and others.

**[0045]** ~~In the below~~ Hereinbelow, the data processors according to the first to fifth embodiments are each described in detail. Specifically, the data processors of the first to third, and fifth embodiments correspond to the mobile unit 20 in FIG. 1, and the data processor of the fourth embodiment corresponds to the server 1 in FIG. 1. In those data processors of the first to third, and fifth embodiments, the CPU 31 executes programs stored in the RAM

32 or the ROM 33 according to the respective embodiments.

[0046]     {First Embodiment}

FIG. 3 is a block diagram showing the structure of a data processor 100 according to the first embodiment of the present invention. As shown in FIG. 3, ~~to the communications network 10,~~ a server 1a and the data processor 100 are connected to the communications network 10. The server 1a stores data written in HTML, XML, or the like, ~~and as well as~~ image data, and forwards such data in response to any data request coming from the data processor 100. To retrieve any data from the server 1a, the data processor 100 first receives ~~from the server 1a~~ command data 111 including any command for the data processor 100 from the server 1a. Then, in accordance with the command data 111, the data processor 100 retrieves data which is originally intended to ~~retrieve~~ be retrieved from the server 1a. The data eventually retrieved from the server 1a is referred to as terminal data 112, and is used to control the data processor 100.

[0047]     The command data 111 includes, as address information for specifying the terminal data 112, a URL (Uniform Resource Locator) of the corresponding terminal data 112. Here, the terminal data 112 is presumably image data to be displayed on the screen, for example, icon image data. In response to the user's operation, the data processor 100 retrieves the terminal data 112 for screen display. ~~Assuming~~ Assume here that the terminal data 112 is retrieved and updated always ~~in~~ according to the above

procedure, i.e., command data is received first, and terminal data follows in accordance with the received command data. In this sense, the data processor 100 may be referred to as an information terminal device.

5   **[0048]**     As shown in FIG. 3, the data processor 100 includes a data request section 101, a transmission/reception section 102, a received data storage section 103, an analysis section 104, an analysis result storage section 105, a validity determination section 106, an operation control section 107, a terminal data  
10   storage section 108, and a display section 109. In response to the user's request, the data request section 101 specifies which command data 111 is to be received from the server 1a. The transmission/reception section 102 transmits/receives data to/from the server 1a connected to the communications network 10.  
15   The received data storage section 103 stores the data received by the transmission/reception section 102.

20   **[0049]**     The analysis section 104 analyzes the command data 111 stored in the received data storage section 103. The analysis result storage section 105 stores the result of analyzing the command data 111 by the analysis section 104. Based on the analysis result thus stored in the analysis result storage section 105, the validity determination section 106 determines whether or not the received command data 111 is valid ~~or not~~. When the received command data 111 is determined as valid, the analysis result is  
25   used as the basis for the operation of the operation control section

107. In a case where the URL included in the command data 111 is the one for the terminal data 112, for example, the operation control section 107 ~~so~~ controls the transmission/reception section 102 so as to retrieve the terminal data 112 from the server 1a.

5 [0050] ~~Thus~~ The retrieved terminal data 112 is stored in the terminal data storage section 108. Under conditions which will be described later, the operation control section 107 writes the data stored in the received data storage section 103 to the terminal data storage section 108. The display section 109 displays on

10 its screen the terminal data 112 stored in the terminal data storage section 108. Here, data writing to the terminal data storage section 108 is allowed only for the operation control section 107.

[0051] FIG. 4 is a flowchart showing a terminal data updating process which is executed by the data processor 100. First, in

15 a data requesting process (step S110), the data request section 101 receives a data request of the command data 111 from the user. To make such a data request, the user selects any anchor on the screen displayed by a Web browser.

[0052] Then, in a command data receiving process (step S120),

20 the transmission/reception section 102 receives the command data 111 specified in step S110 from the server 1a. More specifically, the transmission/reception section 102 first forwards a request of the command data 111 to the server 1a, and correspondingly, receives the command data 111 from the server 1a. ~~Thus~~ The received

25 command data 111 is stored in the received data storage section

103.

[0053] Next, in a command data analyzing process (step S130), the analysis section 104 analyzes the command data 111 stored in the received data storage section 103. The result of analyzing the command data 111 is stored in the analysis result storage section 105.

[0054] Then, in a command data validity determining process (step S140), based on the analysis result stored in the analysis result storage section 105, the validity determination section 106 determines whether or not the received command data 111 is valid. If the command data 111 is determined as valid, the procedure goes to step ~~S150, otherwise~~ S150. Otherwise, this is the end of the terminal data updating process without the procedure going to step S150 and onward.

[0055] Next, in an operation controlling process (step S150), the operation control section 107 operates in accordance with the received command data 111. If the command data 111 includes the URL of the terminal data 112, the operation control section 107 ~~se-~~controls the transmission/reception section 102 so as to retrieve the terminal data 112 from the server 1a. Here, if the command data 111 includes several of the URLs of the terminal data 112, the operation control section 107 retrieves the terminal data 112 for the corresponding number of ~~times~~ URLS. The retrieved terminal data 112 is then stored in the received data storage section 103.

[0056] Then, in a displaying process (step S160), the operation control section 107 writes the terminal data 112 retrieved in step S150 to the terminal data storage section 108. The display section 109 then displays on its screen the terminal data 112 stored in the terminal data storage section 108. By sequentially executing ~~a~~the sequence of processes of FIG. 4, the terminal data 112 specified by the command data 111 is retrieved from the server 1a, and is displayed on the screen of the data processor 100.

[0057] FIGS. 5 and 6 show examples of the command data 111 and the terminal data 112, respectively. FIG. 5 shows exemplary command data 140, which is a specific version of the command data 111 in XML. In the command data 111, any part between <character string X> and </character string X> is referred to as an "X tag". In the command data 140, a protected tag 141, a dataSourceUrl tag 142, a signature tag 144, and a certificate tag 145 are used in the command data validity determining process (step S140). An exDataDigest tag 143 is used in a terminal data validity determining process (step S153 of FIG. 10, which will be described below). The protected tag 141 includes commands for the data processor 100. In the example of FIG. 5, it is commanded ~~is~~ to "Customize" the display screen by accessing two URLs in the dataSourceUrl tag 142 and retrieving the corresponding two terminal data.

[0058] FIG. 6 shows an example of the terminal data 112. In FIG. 6, the rows of the table each correspond to one terminal data. The left column indicates the contents of the corresponding

terminal data, and the right column indicates the URL of the corresponding terminal data. Exemplarily shown in FIG. 6 as the terminal data are image data of a fowl, and that of a panda. The dataSourceUrl tag 142 in the command data 140 of FIG. 5 carries  
5 URLs for each of such terminal data.

**[0059]** Referring to FIG. 7, described in detail next is the command data analyzing process (step S130). ~~Assuming~~ Assume here that the command data 111 in the server 1a has been encrypted by using a DES (Data Encryption Standard) algorithm. In such a case,  
10 the command data 111 received in the command data receiving process (step S120) remains encrypted. Thus, in a decrypting process (step S131), the analysis section 104 decrypts the command data 111. Then, in ~~the~~ a command data analyzing process (step S132), the analysis section 104 segments the decrypted command data into  
15 components. The analysis result is stored in the analysis result storage section 105. Here, if the command data 111 has not been encrypted, the procedure jumps to the command data analyzing process (step S132) without going through the decrypting process (step S131).

20 **[0060]** The analysis result storage section 105 stores the result of analyzing the command data 111 while pairing tag names with data. FIG. 8 shows the result of analyzing the command data 140. In this example, "descriptorType" ~~which~~ is information identifying what the command data is commanding and is paired with "Customize".  
25 "FID" ~~which~~ is information indicating the version of the command



data and is paired with "1". "dataSourceUrl" ~~which~~ defines, by URL, what terminal data is to be retrieved by the operation control section 107 now having received the command data is paired with "https://www.hoge.com/fool.gif" and another "dataSourceUrl" is  
5 paired with "https://www.hoge.com/foo2.gif". "exDataDigest" ~~which~~ is information that is derived by hashing the URLs of the terminal data under the MD5 (Message Digest 5) algorithm and is paired with "afdfsafafafkljk:jbahafldjfa", and another "exDataDigest" is paired with "bhouybyouhsdholidiouybs".  
10 "signature" is paired with the signature found in the signature tag 144. "certificate" is paired with the signer certificate found in the certificate tag 145, and another "certificate" is paired with the certificate of secondary CA (Certificate Agency). Here, depending on the contents of the command data 111, the analysis  
15 result may not include ~~no~~ a certificate of secondary CA, or may include certificates of tertiary CA and quaternary CA together with the certificate of secondary CA.

**[0061]** Referring to FIG. 9, the command data validity determining process (step S140) is now described in detail. ~~In~~  
20 ~~the below,~~ Hereinbelow, exemplarily, the command data 140 is the one which is determined whether to be valid or not. First, in a hashing process (step S141), the validity determination section 106 hashes, out of the command data 140, the data between <protected> and </protected> by using the MD5 algorithm.

25 **[0062]** Next, in a certificate acquiring process (step S142),

the validity determination section 106 extracts, one by one, the certificates stored under the "certificate" from the analysis result storage section 105. In this example, the validity determination section 106 extracts the signer certificate first, and then extracts the certificate of secondary CA, and if ~~including~~ included, the certificate of tertiary CA, ~~and then~~ followed by the certificate of quaternary CA. Here, presumably, the certificate is the one which is adopted in the digital signature using public key cryptosystem, which is popular ~~in~~ on the Internet.

10 **[0063]** Next, in a certificate determining process (step S143), the validity determination section 106 uses the certificates so far acquired to determine whether or not the signer certificate is valid ~~or not~~. Specifically, the validity determination section 106 determines whether or not the signer certificate is valid ~~or not~~ firstly first by using only the signer certificate, secondly by using the certificate of secondary CA together with the signer certificate, and thirdly by using, if ~~including~~ included, the certificate of tertiary CA together with the signer certificate and the certificate of secondary CA. If the signer certificate cannot be proved as valid (NO in step S143), the procedure goes back to step S142. If this is the case, the data processor 100 acquires any new certificate to try to determine the validity of the signer certificate again.

20 **[0064]** If the signer certificate is proved as valid (YES in step S143), the procedure goes to step S144 and onward. In a public

25

key acquiring process (step S144), the validity determination section 106 acquires a public key from the signer certificate. In a signature decrypting process (step S145), the validity determination section 106 then uses the public key acquired in  
5 step S144 to decrypt the signature in the signature tag 144. In this manner, the signature that is applied to the command data can be derived. Next, in a hash value comparing process (step S146), the validity determination section 106 compares the hash value calculated in step S141 with the signature derived in step  
10 S145. ~~If these~~ the calculated hash value and the derived signature are the same, the validity determination section 106 determines that the command data 140 is valid. This is the end of the command data validity determining process.

**[0065]** Here, if no certificate is newly acquired in the  
15 certificate acquiring process (NO in step S142), or if ~~these two values are not the same~~ the calculated has value and the derived signature are determined not to be the same value in the hash value comparing process (step S146), that is the end of the terminal data updating process.

**[0066]** Referring to FIG. 10, the operation controlling process  
20 (step S150) is now described in detail. First, in a URL retrieving process (step S151), the operation control section 107 sequentially retrieves, one by one, the URLs of the terminal data 112 stored in the analysis result storage section 105. Then, in a terminal  
25 data retrieving process (step S152), the operation control section

107 controls the transmission/reception section 102, accesses the URLs acquired in step S151, and resultantly retrieves the terminal data 112 from the server 1a.

5     **[0067]**     Next, in ~~the a~~ terminal data validity determining process (step S153), the operation control section 107 determines whether ~~thus retrieved or not the~~ terminal data retrieved in the terminal data retrieving process (step S152) is valid ~~or not~~. ~~Stored in the analysis result storage section 105 are, as~~ As the analysis result of the command data 111, values derived by hashing the  
10     terminal data 112 using the MD5 are stored in the analysis result storage section 105. Accordingly, the operation control section 107 hashes the retrieved terminal data by also using ~~also~~ the MD5 algorithm, and when the resultant hash value is the same as the hash value already stored in the analysis result storage section  
15     105, the retrieved terminal data is determined as valid. If the command data 111 ~~carries no~~ does not carry such a result of hashing the terminal data 112, the procedure may skip step S153.

20     **[0068]**     As such, after the retrieved terminal data is determined as valid in the terminal data validity determining process (YES in step S153), the procedure goes to ~~the a~~ terminal data storing process (step S154). In this process, the operation control section 107 writes the retrieved terminal data to the terminal data storage section 108. Then, the procedure goes to step S152 to process the next terminal data. If every URL included in the  
25     command data is through with a sequence of processes from steps

S151 to S154 (NO in step S151), this is the end of the operation controlling process.

[0069] FIG. 11 shows how the display screen changes as a result of updating the terminal data. The display section 109 performs  
5 screen display based on the terminal data stored in the terminal data storage section 108. ~~Assuming~~ Assume here that, prior to updating the terminal data, ~~displayed is a screen 181. And 181~~  
is displayed and the user changes two icons thereon through his/her operation. Responding to such user's operation, the data  
10 processor 100 receives the command data 140, and in accordance therewith, receives two types of image data as shown in FIG. 6.  
By the data processor 100 writing ~~thus~~ this received image data to the terminal data storage section 108, a screen 182 appears.

[0070] As described in the above, according to the data  
15 processor of the ~~present~~ first embodiment, a screen update can be securely done by allowing the terminal data to be updated only in a fixed procedure.

[0071] ~~{Second Embodiment}~~

FIG. 12 is a block diagram showing the structure of a  
20 dataprocessor 120 according to the second embodiment of the present invention. In the data processor 120 of FIG. 12, a data output section 129 is provided as an alternative to the display section 109 in the data processor 100 of the first embodiment. Further,  
the operation control section in ~~this~~ the second embodiment  
25 operates differently from that in the first embodiment, and thus

is under the different reference numeral of 127. Herein, any constituent which is identical to that in the first embodiment is provided with the same reference numeral, and is not described again.

5 [0072] As shown in FIG. 12, ~~to the communications network 10,~~ a server 1b and the data processor 120 are connected to the communications network 10. Note that, the server 1a of the first embodiment stores the command data 111 and the terminal data 112 separately, but ~~stored in the server 1b of the present second~~  
10 embodiment is stores command data 131 which ~~is initially including~~ includes one or more terminal data 132.

[0073] FIG. 13 is a flowchart showing the terminal data updating process which is executed by the data processor 120. Here, steps S110 to S140 of FIG. 13 are the same as those in the first ~~embodiment,~~  
15 ~~and thus embodiment.~~ Thus, these steps are provided with the same step numbers, and no further description is given here.

[0074] After the command data validity determining process (step S140), the procedure goes to an operation controlling process (step S170), which is different from the operation controlling  
20 process (step S150) in the first embodiment. In this operation controlling process (step S170), the operation control section 127 operates in accordance with the received command data. Herein, since the command data comes together with the terminal data, receiving the command data means also retrieving ~~also~~ the terminal  
25 data.

[0075] Then, in a terminal data outputting process (step S180), the operation control section 127 writes the terminal data retrieved in step S170 to the terminal data storage section 108. The data output section 129 reads the terminal data thus stored  
5 | in the terminal data storage section 108, and outputs ~~it~~ the read terminal data to the outside of the data processor 120. By sequentially going through the processes of FIG. 13, the command data 131 is forwarded from the server 1b, and the terminal data 132 included in the command data 131 is outputted to the outside  
10 | of the data processor 120.

[0076] FIG. 14 shows examples of the command data 131 and the terminal data 132. Command data 160 of FIG. 14 is a specific version of the command data 131 in XML. In the command data 131, any part between <character string X> and </character string X> is referred  
15 | to as an "X tag". ~~Similarly~~ Similar to the first embodiment, in the command data 160, a protected tag 161, a signature tag 164, and a certificate tag 165 are used in the command data validity determining process (step S140). The protected tag 161 includes any command for the data processor 120. In the example of FIG.  
20 | 14, it is ~~is~~ commanded to "Control" the data output section 129 by using the data in the cntlData tag 162 ("123"). In this sense, the data "123" corresponds to the terminal data 132. Presumably, the command data 131 in the server 1b has been, as in the first embodiment, encrypted by using the DES algorithm, for example.

25 | [0077] FIG. 15 shows the analysis result of the command data

160. FIG. 15 is different from FIG. 8 in the following respect:

"descriptorType" ~~for indicating~~ indicates what the command data is commanding and is paired with "Control", and "ctrlData" is newly included for indicating what terminal data is to be retrieved by the operation control section 127 having received the command data, and paired therewith is "123".

[0078] Referring to FIG. 16, the operation controlling process (step S170) is now described in detail. First, in a terminal data retrieving process (step S171), the operation control section 127 sequentially retrieves, one by one, the terminal data stored in the analysis result storage section 105. Then, in a terminal data storing process (step S172), the operation control section 127 writes the retrieved terminal data to the terminal data storage section 108. Thereafter, the procedure goes to step S171 to process the next terminal data. If every terminal data has been processed for the current command data (NO in step S171), this is the end of the operation controlling process.

[0079] As such, according to the data processor 120 of the ~~present~~ second embodiment, the data processor 120 can be securely controlled by updating the terminal data only in a fixed procedure.

[0080] In the first and second embodiments, the operation control sections 107 and 127 are configured by the CPU 31 executing the programs stored in the RAM 32 or the ROM 33. Specifically, the operation control sections 107 and 127 may be configured by the CPU 31 executing a JAVA applet stored in the RAM 32 as a JAVA



virtual machine. If this is the case, the JAVA applet may be dynamically downloaded to the data processors 100 and 120 over the communications network 10 responding to the user's command. Moreover, in the above, the data processors 100 and 120 store the  
5 terminal data 112 retrieved based on the command data 111 (or the terminal data 132 retrieved from the command data 131) into the terminal data storage section 108. This is not restrictive, and such terminal data may be directly outputted to any data output section provided in peripheral equipment, an IrDA (Infrared Data  
10 Association) communications interface section, or the like.

**[0081]** Further, the data processors 100 and 120 may retrieve the command data 111 and 131 by any other means except communications. For example, recording media may be used for the purpose of  
retrieving the command data 111 and 131. In the command data 111  
15 and 131, the tags are not restricted in format, and may be in a format of "tag name: value" or others. The encryption system applied to the command data 111 and 131 is arbitrary, and is not  
limited to the DES algorithm. In the command data validity determining process (step S140), the validity of the signer  
20 certificate may be determined by any other means except for public key cryptosystem. The hash algorithm in steps S141 and S153 may be any other algorithm except for the MD5. In step S141, the command data 111 and 131 may not necessarily be entirely hashed, and the region for the purpose may be determined as required. Since the  
25 command data is hashed for the purpose of comparison between the

resultant hash value and the result of decrypting the signature, the process in step S141 may be carried out at any arbitrary timing before step S146. Further, in step S144, the public key is acquired from the certificate of the signer included in the command data. This is not restrictive, and the public key may be acquired in other manners as long as the public key of the signer can be correctly acquired. As an example, in step S144, the public key may be acquired from the signer's certificate which has been previously stored in the data processors. The terminal data 112 and 132 are not restricted to be image data, and may be music data, control data, or the like.

**[0082]** In the first embodiment, the command data 111 includes the URL(s) of the terminal data 112. Alternatively, the command data 111 may include identification information for uniquely specifying the terminal data 112, and the data processor 100 may use the identification information to derive the URL(s) of the terminal data 112. Also, the command data includes the hash value of the terminal data 112, and this hash value is used in step S153 to determine whether or not the command data 111 is valid ~~or not~~. This is not restrictive, and the command data 111 may include a checksum or data size of the terminal data 112, and in step S153, it may be used to determine the validity of the command data. Alternatively, step S153 may be skipped. Furthermore, the command data 111 and the terminal data 112 may be stored in different servers.

**[0083]** {Third Embodiment}

FIG. 17 is a block diagram showing the structure of a data processor 200 according to the third embodiment of the present invention. As shown in FIG. 17, ~~to the communications network 10,~~ a server 1c and the data processor 200 are connected to the communications network 110. The server 1c stores data written in HTML or XML, for example, and image data, and forwards data in response to any request coming from the data processor 200. In the ~~present~~ third embodiment, there is no limitation for the procedure of the data processor 200 to retrieve data from the server 1c. As an example, the data processor 200 may forward the data request to the server 1c responding to the user's operation.

**[0084]** As shown in FIG. 17, the data processor 200 includes a reception section 201, a signature authentication section 202, an unprotected data authentication section 203, and an application section 204. The reception section 201 receives data from the server 1c connected to the communications network 10. As to the received data, the signature authentication section 202 authenticates its digital signature. The unprotected data authentication section 203 checks the validity of any data determined as not ~~to be~~ being protected by means of a digital signature. The application section 204 uses the received data for various operations.

**[0085]** FIG. 18 is a diagram showing the structure of data to be processed by the data processor 200. Data 240 of FIG. 18 includes a protected data region 241, an unprotected data region 242, and

an authentication information region 243. The protected data region 241 carries data to be protected by digital signature. The unprotected data region 242 carries data that is not to be protected by digital signature. The authentication information region 243 includes a signature and a public key for digital signature. The protected data region 241 also carries ~~also~~ an unprotection list 245, which shows a listing of a data type in the unprotected data region 242.

**[0086]** Referring to FIGS. 17 and 18, the operation of the data processor 200 is now described. The reception section 201 receives data from the server 1c wirelessly or through cables. ~~In the below~~ Hereinbelow, the data 240 of FIG. 18 is assumed to be received. The reception section 201 outputs the received data 240 to the signature authentication section 202.

**[0087]** The signature authentication section 202 checks, based on authentication information included in the authentication information region 243 of the data 240, the data in the protected data region 241 for any possibility of data tampering or data error. To be specific, the authentication information region 243 includes a signature as the result of hashing the protected data region 241, and then encrypting the result by using a private key, and a public key which pairs off with the private key. The signature authentication section 202 extracts the signature and the public key from the authentication information region 243, and then decrypts the signature by using the public key. Then, the

decryption result is compared with the result of the hashing of  
the protected data region 241, and if ~~these~~ the decryption result  
and the hashing result are the same, it means that the data in  
the protected data region 241 is correct, i.e., the data has not  
5 been tampered or no data error has occurred thereto. If so, the  
signature authentication section 202 outputs, to the unprotected  
data authentication section 203, both the data in the protected  
data region 241 and the data in the unprotected data region 242.

**[0088]** The unprotected data authentication section 203 refers  
10 to the unprotection list 245 in the protected data region 241 for  
checking whether ~~correctly showing~~ the data type listing of the  
unprotected data region 242 is correctly shown. Here, the  
unprotection list 245 itself has been confirmed as being correct  
by the signature authentication section 202. Therefore, in the  
15 case where the unprotected data region 242 includes any data type  
that is not listed in the unprotection list 245, it means that  
some data tampering or data error has occurred to the unprotected  
data region 242 and thus a data type change has followed, or the  
data is not needed by the application section 204. Accordingly,  
20 the unprotected data authentication section 203 discards such type  
of data not listed in the unprotection list 245, and outputs the  
rest of the data whose type is listed in the unprotection list  
245 from the unprotected data region 242 to the application section  
204 together with the data in the protected data region 241.

25 **[0089]** ~~In the below~~ Hereinbelow, further descriptions are given

while exemplifying the received data as being hypertext data. FIG. 19 shows an example of the data 240, i.e., text data 260, to be processed by the data processor 200. The text data 260 of FIG. 19 is data for schedule update which is written in XML. ~~Assuming~~  
5 Assume here is, that using XML of the ~~present third~~ embodiment results in tagging the digital signature by using public key cryptosystem.

[0090] In FIG. 17, the server 1c and the data processor 200 presumably work together to manage one schedule data. The schedule  
10 data is presumably stored separately in the server 1c and the data processor 200, and updated as appropriate. In this system, the server 1c and the data processor 200 have to establish a synchronization therebetween to keep the schedule data the same.  
For ~~the~~ this purpose, the data processor 200, as a client, requests  
15 the server 1c to establish such a synchronization therewith. In response, the server 1c forwards such text data 260 as shown in FIG. 19 to the data processor 200. The text data 260 includes an update operation command, the schedule data, update information about day and time, a session ID of the current update session,  
20 and the like. Here, the update operation command indicates which of the server and the client is prioritized for a schedule update.

[0091] In the text data 260, any part between <character string X> and </character string X> is referred to as an "X tag". A protected tag 261 corresponds to the protected data region 241  
25 of FIG. 18. An unprotected tag 262 corresponds to the unprotected

data region 242 of FIG. 18. A signature tag 263 and a certificate tag 264 correspond to the authentication information region 243 of FIG. 18. The signature tag 263 includes a signature 277. The signature 277 is the one which is derived by hashing the protected tag 261 being the protected data region, and by encrypting the resultant hash value by using a private key on the transmission end. The certificate tag 264 includes a public key 278 which pairs off with the private key on the transmission end. The protected tag 261 includes an unprotectedTag tag 265. The unprotectedTag tag 265 shows a listing of a data type included in the unprotected tag 262, which is the unprotected data region. Here, the unprotectedTag tag 265 corresponds to the unprotection list 245 of FIG. 18.

**[0092]** The protected tag 261 corresponding to the protected data region 241 carries data which should not be tampered with. In the schedule update data shown in FIG. 19, regarded as such data not to be tampered with are the update operation command, the schedule data, and a return URL for forwarding the next request to the server. Thus, the protected tag 261 carries a command tag 271 including the update operation command, a schedule tag 272 including the schedule data, and a returnUrl tag 273 including the return URL.

**[0093]** On the other hand, the unprotected tag 262 corresponding to the unprotected data region 242 carries temporary information ~~which is allowed for tampering~~ to be tampered with. In the schedule

update data of FIG. 19, regarded as such data are the session ID and the update information about day and time. Thus, the unprotected tag 262 carries a sessionID tag 274 including the session ID, and a modified tag 275 including the update information about day and time. Here, as a result of data tampering, a command tag 276 is assumed to be located in the unprotected tag 262.

**[0094]** Referring to FIG. 20, described next is the operation of the data processor 200 for outputting the received data to the application section 204. First, the reception section 201 receives data from the server 1c connected to the communications network 10 (step S201). ~~In the below~~ Hereinbelow, exemplified is a case where the text data 260 of FIG. 19 is received.

**[0095]** Next, the signature authentication section 202 hashes the protected tag 261 corresponding to the protected data region 241 (step S202). The signature authentication section 202 then uses the public key 278 to decrypt the signature 277 (step S203). Here, the signature authentication section 202 may execute steps S202 and S203 in reverse order. The signature authentication section 202 compares the decryption result of the signature 277 with the hash value calculated in step S202 (step S204). ~~If these~~ the decryption result and the calculated has value are not the same (No in step S204), the received data is determined as not being reliable due to some data tampering or error occurred to the protected data region. In this case, the signature authentication section 202 discards the received data (step S205).



Then, the data processor 200 ends the process for the received data without outputting it to the application section 204.

5     **[0096]**     ~~If those two data~~ On the other hand, if the decryption result and the calculated has value are the same in step S204 (YES in step S204), the signature authentication section 202 outputs, to the unprotected data authentication section 203, the unprotectedTag tag 265 in the protected tag 261, and the unprotected tag 262. Thereafter, the unprotected data authentication section 203 refers to the unprotectedTag tag 265 for checking whether

10     ~~carrying~~ all of the tags included in the unprotected tag 262 are carried (step S206). If there is any tag (undefined tag) not found in the unprotectedTag tag 265 which is the one corresponding to the unprotection list 245 (YES in step S207), it means that the tag has been tampered or is not needed by the application section

15     204. If so, the unprotected data authentication section 203 discards data included in such undefined tag(s) (step S208).

20     **[0097]**     The unprotected data authentication section 203 outputs, to the application section 204, the data included in the protected tag 261, and the data in the unprotected tag 262 (~~step S208~~ S209). Here, the data in the protected tag 261 has been confirmed as having not been tampered with. Among the data included in the unprotected tag 262, any data whose type is not found in the unprotectedTag tag 265 has been eliminated due to effects of the unprotected data authentication section 203.

25     **[0098]**     In the text data 260, "SESSIONID" which is the data type

of the sessionID tag 274, and "MODIFIED" which is the data type of the modified tag 275 are included in the unprotectedTag tag 265. Thus, the sessionID tag 274 and the modified tag 275 are both outputted to the application section 204. On the other hand,  
5 "COMMAND" which is the data type of the command tag 276 is not included in the unprotectedTag tag 265. ~~It~~ "COMMAND", as the data type of the command tag 276, means that the command tag 276 might have been tampered with, and thus the data is determined as not being reliable. Therefore, the unprotected data authentication  
10 section 203 discards the command tag 276 without outputting ~~it~~ the command tag 276 to the application section 204.

[0099] Here, as to the data provided by the unprotected data authentication section 203, the application section 204 has no need to know which of the protected data region and the unprotected  
15 data region has included the data. This is because, by then, the tags have been confirmed as being correct due to the effects of the signature authentication section 202 and the unprotected data authentication section 203, and the data included in the  
unprotected data region is the one which is originally allowed  
20 for tampering. If data tampering is partially allowed, the data type may be eliminated from the unprotection list, and the data may be allocated to the protected data region.

[0100] As such, according to the data processor of the ~~present~~ third embodiment, the unprotection list provided in the protected  
25 data region shows types of data that are included in the unprotected

data region. When the data is hypertext, the unprotection list  
also shows the types of tags that are included in the unprotected  
data region. Any data (or tag) type included in the unprotected  
data region but not listed in the unprotection list is not provided  
5 | to the application ~~execution~~ section. In this manner, as compared  
with the case where the data is subjected to data signature in  
its entirety, the data amount to be used for signature  
authentication can be reduced, successfully improving the  
efficiency for signature authentication. Moreover, since only  
10 | the data (or tag) whose type is found in the unprotection list  
is forwarded to the application section, the data (or tag) included  
in the unprotected data region can be increased in reliability.  
Further, the application section has no need to know whether the  
data (or tag) has been included in which of the protected data  
15 | region or the unprotected data region for processing the received  
data. As a result, the application section can be reduced in  
processing amount, thereby ~~rendering~~ increasing the processing  
speed ~~increased~~.

**[0101]**     ~~{Fourth Embodiment}~~

20 |             FIG. 21 is a block diagram showing the structure of a  
data processor 220 according to the fourth embodiment of the present  
invention. As shown in FIG. 21, ~~to the communications network~~  
10 | ~~10,~~ the data processors 200 and 220 are both connected to the  
communications network 10. ~~In the below~~ Hereinbelow, for  
25 | distinction therebetween, the data processor 220 is referred to

as a transmitting data processor, while the data processor 200  
| is referred to as a receiving data processor. The receiving data  
processor 200 is the data processor according to the third  
embodiment, and the transmitting data processor 220 generates the  
5 data 240 of FIG. 18 for transmission.

[0102] As shown in FIG. 21, the transmitting data processor  
220 includes an input section 221, an unprotection list generation  
section 222, a data arrangement section 223, a signature generation  
section 224, and a transmission section 225. The input section  
10 221 is used to input data to be transmitted, and its data type  
| is to be listed in the unprotection list 245. Based on the data  
type included in the unprotected data region 242, the unprotection  
list generation section 222 generates the unprotection list 245.  
| According to ~~thus~~ the generated unprotection list 245, the data  
15 arrangement section 223 arranges the transmitting data into the  
protected data region 241 and the unprotected data region 242.  
For the data included in the protected data region 241, the signature  
generation section 224 generates the authentication information  
region 243 for detecting any possibility of data tampering. The  
20 transmission section 225 forwards the data to the receiving data  
processor 200 connected to the communications network 10.

[0103] For data transfer from the transmitting data processor  
220 to the receiving data processor 200, inputted into the input  
section 221 in the transmitting data processor 220 is the data  
25 type found in the unprotected data region 242. Based on the data

type coming from the input section 221, the unprotection list generation section 222 accordingly generates the unprotection list 245. The resultant unprotection list 245 is handled as data to be arranged in the protected data region 241.

5   **[0104]**     Based on the resultant unprotection list 245, the data arrangement section 223 determines to which of the protected data region 241 and the unprotected data region 242 the transmitting data is to be arranged. The data arrangement section 223 follows  
10   ~~the~~ this determination to arrange the transmitting data either in the protected data region 241 or the unprotected data region 242. Specifically, the data arrangement section 223 arranges the data into the unprotected data region 242 when its data type is found in the unprotection list 245, and otherwise arranges the  
15   ~~date~~ into the protected data region 241.

15   **[0105]**     The signature generation section 224 hashes the data included in the protected data region 241 together with the  
20   unprotection list 245, and encrypts the resultant hash value by using a private key. The resultant value will be the signature for the transmitting data. The signature generation section 224  
25   arranges a public key which pairs off with the private key and the resultant signature to the authentication information region 243 of the transmitting data. In this manner, the transmitting data is affixed with the signature. The transmission section 225  
forwards ~~thus~~ the signed data to the receiving data processor 200.  
The receiving data processor 200 operates in ~~the similar~~ a manner

similar to that described above in the third embodiment.

[0106] ~~In the below~~ Hereinbelow, further descriptions are given while exemplifying a case where the data to be transferred is hypertext data. FIG. 22 shows an example of the data 240, i.e., text data 280 and 290, to be processed by the transmitting data processor 220. The text data 280 and 290 of FIG. 22 are, as the text data 260 of FIG. 19, data for a schedule update written in XML. Here, as in the third embodiment, using XML of the ~~present~~ fourth embodiment results in tagging the digital signature made by a public key cryptosystem, and the conditions in which the text data 280 and 290 are ~~used, and~~ used as well as the meaning of the tags included in the text data 280 and 290 are the same as the third embodiment. In FIG. 22, any component identical to that in the third embodiment is under the same reference numeral, and is not described again.

[0107] Described next is a case where the modified tag 275 in the text data 280 is changed in state, from unprotected to protected. To the input section 221 of FIG. 21, inputted is the data type to be included in the unprotected data region. At this time, the type of the modified tag 275 is not inputted as the data type to be included in the unprotected data region. The unprotection list to be generated by the unprotection list generation section 222 thus ~~include~~ includes no "MODIFIED" which is the data type of the modified tag 275. In FIG. ~~23~~ 22, an unprotectedTag tag 295 corresponds to the resultant unprotection list. Based on such

an unprotection list, the data arrangement section 223 rearranges the modified tag 275 which has been arranged in the unprotected tag 282 corresponding to the unprotected data region into a protected tag 291 corresponding to the protected data region. Thus,  
5 unprotected tag 292 in the text data 290 is equivalent to a result obtained by removing the modified tag 275 from the unprotected tag 282 in the text data 280. The signature generation section 224 hashes the protected tag 291 to derive a signature that is to be included in a signature tag 293. The signature tag 293 and  
10 the certificate tag 264 structures the authentication information region. The signature generation section 224 adds ~~thus~~ the generated authentication information region to the transmitting data. In this manner, the data 290 can be derived in which the data has been partially changed in state. The transmission section  
15 225 forwards ~~thus~~ the derived data 290 to the receiving data processor 200.

[0108] As described in the above, according to the data processor of the ~~present~~ fourth embodiment, the data type of whatever is included in the unprotected data region is first  
20 inputted, and in accordance therewith, the unprotection list is generated and arranged into the protected data region. When the data is hypertext data, the unprotection list ~~shows~~ also shows the tag type of whatever is included in the unprotected data region. Based on the resultant unprotection list, the transmitting data  
25 (or tag) is determined to which region to go, i.e., the protected

data region or unprotected data region. Thus, the data (or tag) can be changed in state as appropriate, from unprotected to protected and vice versa, with exactly the same processes for the application section in the receiving data processor or any other  
5 processes. Consequently, data handling can be freely changed.

[0109] ~~Similarly~~ Similar to the third embodiment, as compared with the case where the data is subjected to digital signature in its entirety, the data amount for signature authentication can be reduced, thereby improving the efficiency in signature  
10 authentication. Moreover, the data (or tag) in the unprotected data region can be increased in reliability, and the application section in the receiving data processor has no need to make it clear which data region has included the data (or tag), i.e., the protected data region or the unprotected data region, to process  
15 the data (or tag).

[0110] In the third and fourth embodiments, as shown in FIG. 18, the protected data region 241, the unprotected data region 242, and the authentication information region 243 are arranged in order as shown in FIG. 18. Alternatively, those regions may  
20 be arranged in any arbitrary order as long as ~~those~~ they remain distinguishable from each other. Further, as are any other data in the protected data region 241, the unprotection list 245 in the protected data region 241 is not limited in arrangement position  
as long as ~~it~~ the unprotection list 245 will be subjected to signature  
25 authentication.



[0111] In the case where the data is hypertext data, as shown in FIGS. 19 and 22, the unprotection list 245 includes the tag type of whatever is included in the unprotected data region 242. Instead of the tag type(s), the tag(s) themselves may be included, or any other representations (e.g., tag IDs or representations in meta languages for sets of tags) as long as ~~those~~ they remain identifiable as not to be protected.

[0112] In the fourth embodiment, inputted into the input section 221 is a data type (or tag type) to be listed in the unprotection list 245. This is not restrictive, and inputted into the input section 221 may be a data type (or tag type) included in the protected data region. This is because information provided by the input section 221 only needs to identify what data (or tag) is to be arranged to which data region, i.e., the protected data region or the unprotected data region. Alternatively, the unprotection list generation section 222 may be provided with a storage section for storing the data type (or tag type) of whatever is included in the unprotection list 245, and the input section 221 may receive any data (or tag) type of only those that are changed in the current process.

[0113] ~~Fourth Embodiment~~

FIG. 23 is a block diagram showing the structure of a data processor 300 according to the fifth embodiment of the present invention. As shown in FIG. 23, ~~to the communications network~~ 10, a server 10 and the data processor 300 are connected are connected

to the communications network 10. The server 1d stores data written in HTML, or XML, for example, and image data, and forwards data responding to a request coming from the data processor 300. In this sense, the server 1d and the data processor 300 may be referred  
5 to be as a content server and a content processor.

[0114] As shown in FIG. 23, the data processor 300 includes a reception section 301, a signer certificate database 302, and a signature authentication section 303. The reception section 301 receives data from the server 1d connected to the communications  
10 network 10. The signer certificate database 302 stores signer certificates. The signature authentication section 303 searches the signer certificate database 302 for a signer certificate corresponding to the received data, and by using ~~thus the~~ the acquired signer certificate, authenticates the signature that is applied  
15 to the received data.

[0115] FIG. 24 shows an example of data to be received from the server 1d and processed by the data processor 300. ~~In the below~~ Hereinbelow, such data is referred to as a "content". FIG. 25 shows an example of the signer certificate stored in the signer  
20 certificate database 302. In a content 320 of FIG. 24 and a signer certificate 340 of FIG. 25, ~~similarly similar~~ similar to XML, tag names and information corresponding to the tags are represented in a format of "<tag name> information </tag name>". Alternatively, the information corresponding to the tags may be represented in  
25 such a format of "<tag name> information </tag name>". Using such

a format will result in information being hierarchically represented. For reference in the ~~below~~ following description, the content 320 and the signer certificate 340 both carry, on a row basis, line numbers in a format of (number N).

5 [0116] The server 1d stores the content 320 of FIG. 24, and others. The server 1d receives a content request from the data processor 300, and responsively forwards the requested content back to the data processor 300. After receiving the content, the data processor 300 authenticates the content in the following  
10 manner before processing the ~~same~~ content. ~~In the below~~ Hereinbelow, the operation of the signature authentication section 303 is described while assuming that the data processor 300 receives the content 320.

[0117] The signature authentication section 303 first extracts  
15 a signer's name that is included in a signedBy tag under the line number (102) in the content 320. Accordingly, "XYZ. Co., LTD." is extracted as the signer's name. Then, the signature authentication section 303 retrieves, from the signer certificate database 302, a signer certificate corresponding the extracted  
20 signer's name. To be specific, the signature authentication section 303 searches the signer certificate database 302 for a signer certificate whose value of a subject tag is the same as the value of the signdBy tag in the content 320. Here, after searching the signer certificate database 302 as such, the signer  
25 certificate 340 of FIG. 25 is presumed to be retrieved.

[0118] The signature authentication section 303 then checks whether the type of the received content 320 is included in the value of an authorizedContentTypes tag under the line number (205) in the signer certificate 340. The value of the  
5 authorizedContentTypes tag in the signer certificate 340 includes two content types as "adrs" and "sched". In this example, the content type is presumably determined by a characteristic part of a URI (Uniform Resource Identifier), more specifically by an  
10 extension of a URI of the content 320. Accordingly, if the extension of the URI of the received content 320 is either "adrs" or "sched", the signature authentication section 303 determines that the signer is authorized to sign the received content 320.

[0119] Forexample, when the extension of the URI of the received content is "adrs", the signature authentication section 303 uses  
15 a public key which is included in the signer certificate 340 to authenticate the digital signature of the content 320. The public key here is the one that is set as a value of a publicKey tag under the line number (206) in the signer certificate 340. The digital  
signature to be authenticated is the one set which is as a value  
20 of the signature tag under the line number (110) of the content 320.

[0120] To be specific, from the content 320, the signature authentication section 303 extracts character strings under the line numbers from (102) to (108), which are values of a signedInfo  
25 tag under the line numbers (101) to (109). With respect to those

extracted character strings, the signature authentication section 303 applies such a hash algorithm as MD5. Then, the signature authentication section 303 retrieves the public key found under the line number (206) in the signer certificate 340, and the digital signature written as the value of the signature tag under the line number (110) of the content 320. The signature authentication section 303 then decrypts the digital signature by using the public key. The resultant value is then compared with the derived hash value. If ~~these~~ the decrypted digital signature and the derived hash value are the same, the digital signature is determined as valid, and is otherwise determined as invalid and the received content will be discarded.

[0121] As such, according to the data processor of the ~~present~~ fifth embodiment, the signer certificate indicates by the content type whether the signer has an authorization for signing the content. Accordingly, in the same manner for determining such authorization for signature, any new contents in any new applications can be appropriately dealt with.

[0122] In the ~~present~~ fifth embodiment, the content type is defined by the extension of the URI of the content. Instead, the content type may be specified by content identifying information which is included in header information at the time of content reception. Alternatively, the authorizedContentTypes tag in the signer certificate may be allowed to carry, as its value, an asterisk (\*) which indicates a wildcard, and the data processor 300 may

accordingly determine that any signer corresponding to such an  
signer certificate may have an authorization for signing any type  
of contents.

[0123] Further, when receiving a content from the server 1d,  
5 the data processor 300 may also receive a signer certificate  
together therewith from the server 1d. If so, with respect to  
any signers that are not included in the signer certificate  
database 302, the data processor 300 becomes capable of checking  
their authorization. In such a case, certificate authorities may,  
10 in advance, sign the signer certificates to enable the data  
processor 300 to detect their validity when coming from the server  
1d.

[0124] While the present invention has been described in detail,  
the foregoing description is in all aspects illustrative and not  
15 restrictive. It is to be understood that numerous other  
modifications and variations can be devised without departing from  
the scope of the present invention.

ABSTRACT ~~OF THE DISCLOSURE~~

Command data ~~111~~ includes an address of terminal data ~~112~~ to be received. A data processor ~~100~~ first verifies a signature applied to the received command data ~~111~~, and then receives the terminal data ~~112~~ specified by the command data ~~111~~. ~~Thus~~ The received terminal data is used for controlling the data processor ~~100~~ such as a screen display. At this time, the received data may be segmented into a protected data region and an unprotected data region, and any data type included in the unprotected data region may be listed as an unprotection list. If listed, the unprotection list may be arranged in the protected data region. Alternatively, a signer certificate may indicate, by type, what data is signable by its signer, and at the time of data reception, a determination may be made as to whether the signer has ~~an~~ authorization for signing the data classified under the type.